

(19)



Europäisches Patentamt  
European Patent Office  
Office européen des brevets



(11)

**EP 0 794 379 A1**

(12)

## EUROPEAN PATENT APPLICATION

(43) Date of publication:

10.09.1997 Bulletin 1997/37

(51) Int Cl.<sup>6</sup>: F16L 55/172

(21) Application number: 97301447.5

(22) Date of filing: 04.03.1997

(84) Designated Contracting States:

AT BE CH DE DK ES FR GB GR IE IT LI LU MC NL  
PT SE

(30) Priority: 05.03.1996 GB 9604697

(71) Applicant: **AVK Manufacturing Limited**

Dunkirk Lane, Hyde, Cheshire SK14 4PN (GB)

(72) Inventors:

- Hodge, Ian Stuart  
Dukinfield, Cheshire SK16 5QE (GB)
- Madsen, Jens Sonderby  
5700 Svendborg (DK)


(74) Representative: **Ajello, Michael John**

207 Moss Lane  
Bramhall Stockport Cheshire SK7 1BA (GB)

### (54) A pipe repair or jointing collar

(57) A pipe repair or jointing collar, comprising a pair or arcuate segments (10) with clamping means (at 11) for drawing the segments together along an axis (XX) to form a collar around a pipe or a plurality of pipe ends, each segment (10) having an associated sealing member comprising a pair of longitudinally-spaced arcuate sealing strips (21) between the respective ends of which extend a pair of longitudinal sealing strips (20) with

wedge-like members (18) embedded therein adapted to progress generally inwardly each towards the axis (XX) with respect to the segments (10) as the latter are drawn together in order to force the sealing members (20, 21) radially inwards locally of the wedge-like members (18). The integral formation of the sealing members and wedge-like members provide a minimum number of parts to aid assembly of the collar in hazardous conditions.



**FIG.2**

**EP 0 794 379 A1**

## Description

THIS INVENTION concerns split collars for repairing and jointing pipes such as gas pipes and water pipes. Such collars may serve to repair a single damaged pipe, to form a joint between two aligned pipe ends, or to serve as a tee piece to join one pipe with another or others extending at an angle therefrom.

Repair or jointing collars for this purpose take many different forms. Usually they must be designed to correspond very closely with the outer diameter of the pipes thus to ensure a watertight or gas tight seal. Since the collars are designed to be fitted to existing underground mains some of which can be many years old, it is very difficult to ensure that it will always provide an adequate seal. Owing to changing standards, materials, manufacturing techniques and corrosion, pipes of the same nominal diameter can vary widely in actual diameter. Therefore, it is desired that such a collar should be able to accommodate wide variations and differences in pipe diameter.

One known form of repair collar designed for this purpose comprises a pair of arcuate segments whose abutting end faces are inclined with respect to a diametral plane of the collar so that as the segments are drawn together the respective inclined faces undergo relative sliding movement thus squeezing the pipe at a plurality of positions around its circumferences. This requires sufficient resilience or flexibility in the material from which the segments are made so that they may be deformed inwardly to define a smaller radius. However since this kind of arrangement does not ensure a uniform reduction throughout the circumference, certain zones remain in which adequate sealing cannot be assured.

A further known form of repair collar designed to overcome the aforementioned difficulty is described and claimed in patent specification GB 2189000 in which there is provided a collar comprising a pair of arcuate segments with clamping means for drawing the segments together around the pipe, with interposition of one or more corresponding elastomeric arcuate sealing means, and characterised by wedge-like members located between the segments and the sealing means in the region of the clamping means so that the wedge-like members are adapted to slide generally inwardly with respect to the segments as the latter are drawn together thus to force the sealing means radially inwards in those regions.

One disadvantage experienced in the use of collars of this latter kind is that accurate assembly of the segments, the sealing means and the wedge-like members, sometimes presents practical difficulties, particularly since such collars must be assembled on site and sometimes in a very hostile environment. Thus, accuracy of assembly cannot always be guaranteed, and the integrity of a seal provided by the collar is heavily reliant upon accurate assembly and tightening of the separate parts

of the collar.

The present invention seeks to avoid these difficulties at least to a considerable extent.

According to the present invention a pipe repair or jointing collar comprises a plurality of arcuate segments with clamping means for drawing the segments together to form the collar around a pipe or around a plurality of pipe ends, with interposition of corresponding deformable sealing means, each arcuate segment having an associated sealing member, each sealing member comprising a pair of longitudinally spaced arcuate sealing strips between the respective ends of which extend a pair of longitudinal sealing strips, rigid wedge-like members being provided within the segments in the regions of the clamping means and adapted to progress generally inwardly with respect to the segments as the latter are drawn together thus to force the sealing members radially inwards in said regions; characterised in that the wedge-like members are non-removably formed with the sealing members.

Preferably, the wedge-like members are embedded within the longitudinal sealing strips which are integrally formed with the arcuate sealing strips thus to form a one-piece sealing means of rectangular form when laid flat.

Still further, the longitudinal sealing strips include at their respect ends a pair of integral lugs each having means for engagement with a part of a respective arcuate segment whereby each sealing means may be pre-assembled with its respective arcuate segment prior to assembly of the collar.

In one embodiment the collar comprises a pair of arcuate segments and a pair of sealing means each associated with one of the segments, the longitudinal sealing strips of the pair of sealing means having mutually abutting flat faces, the arcuate sealing strips extending to lie co-planar with said flat faces.

Also in a preferred embodiment there is provided at each corner defined by a respective arcuate sealing strip and longitudinal sealing strip a generally triangular strengthening web integrally formed with the arcuate and longitudinal sealing strips.

It is further preferred that the inner arcuate faces of the arcuate sealing strips are curved about an axis transverse to the longitudinal sealing strips.

An embodiment of the invention will now be described with reference to the accompanying drawings, in which:-

Fig. 1 illustrates a pipe repair or jointing collar of the kind previously described in GB 2189000;

Fig. 2 is a vertical cross-section through a pipe repair or jointing collar made in accordance with the invention, as if taken along line II-II of Fig. 1.

and Fig. 3 is an exploded view of a pair of sealing means being part of the collar illustrated in Fig. 2.

Referring now to Fig. 1, the collar illustrated therein includes a pair of generally semi-cylindrical segments

10 of cast iron or a similar rigid material. Each segment 10 has at each end thereof a pair of radially directed bolt-receiving lugs 11 for drawing the segments together by means of bolts 12.

Each segment 10 receives an elastomeric sealing member generally indicated at 13 and consisting of circumferentially ribbed sealing strips 14 and longitudinally ribbed sealing strips 15 and 16. Each strip 16 serves to join adjacent ends of the circumferential strips 14 whilst each strip 15 also extends between the latter but at a circumferential position spaced from their ends. Adjacent each pair of radial lugs 11 and disposed between the body of the segment in this region and the adjacent part of the sealing member 13 is a separate sliding wedge-like member 17. As can be seen from the lower part of Fig. 1, each wedge 13 is retained in position on its associated segment 10 by means of the arcuate sealing strips 14 and the longitudinal sealing strips 15 and 16 with the strips located in respective channels in the wedge.

Internally protruding ribs 18 integral with the segments 10 serve to prevent longitudinal movement of the sealing members 13 and wedges 17.

Each wedge 17 slidably abuts a generally tangential inner face of the associated segment 10. By this means, as the segments are drawn together by bolts 12, after initial contact of the adjacent faces of the respective sealing strips, further closure of the segments 10 will cause the wedges 17 to slide generally inwardly with a component of circumferential movement with respect to the adjacent segment surfaces thus to force the sealing members radially inwards in the regions of the radial lugs 11. Thus, there is substantially uniform reduction in the diameter of the sealing strips around the circumference of the pipe to ensure a good seal thereon substantially without deformation of the segments themselves.

For example, on a nominal 150mm diameter pipe the range of actual diameters which may be accommodated whilst providing an effective seal is at least 20mm.

Referring now to Fig. 2 and in accordance with the present invention, wedge-like inserts 18 of cast iron or aluminium are embedded within and thus formed integrally with the longitudinal sealing strips 20 which are themselves formed integrally with arcuate sealing strips 21 in such a manner that the inner sealing surfaces of the arcuate sealing strips 21 extend upwardly to a flat surface 22 co-planar with a flat surface 23 extending along each longitudinal sealing strip 20.

It can be seen from Fig. 2 that as the segments 10 are drawn together along the axis XX then the wedge-like inserts 18 embedded within the longitudinal sealing strips 20 will tend to move along the adjacent tangential surfaces of the segments, in each case towards the XX axis thereby forcing the arcuate sealing strips inwardly along an axis YY in the region of the radial lugs 11, i.e. where the clamping action on the segments is applied. This inwardly directed sealing effect ensures a uniform circumferential seal without deforming the segments

themselves.

Referring now to Fig. 3 each sealing member can be seen in greater detail as consisting of the longitudinal sealing strips 20 and the arcuate sealing strips 21. The entire sealing member is integrally formed from a resilient material such as natural or synthetic rubber and, when each member is laid flat it is of rectangular form having, at each corner a triangular strengthening web 24, again integrally formed with the arcuate and longitudinal sealing strips.

Extending outwardly in a direction generally radially with respect to the assembled collar is an integral lug 25 having an aperture 26 therein for engagement upon abutments such as are illustrated in Fig. 1 at 27 on the segments 10. Thus, each sealing member may be pre-assembled with its respective segment, no further separate parts being required during final assembly when the two pre-assembled segments with sealing means thereon are brought together and clamped by bolts 12.

Unlike the arcuate sealing strips 14 of Fig. 1, those made in accordance with the invention and illustrated at 21 in Figs. 2 and 3 have smooth inner sealing surfaces which, however, are slightly curved about their respective arcuate axes i.e. in the longitudinal direction of the collar. Similarly, the flat surfaces 23 of the longitudinal sealing strips 20 which are co-planar with similar flat faces 28 at the adjacent ends of the associated arcuate sealing strips 21, are surrounded by slightly inclined surfaces 29 extending inwardly from the outer edges of each longitudinal strip 20.

By extending the arcuate sealing strips right up to the sealing faces of the longitudinal strips integrity of the arcuate sealing strips is ensured.

It is not intended to limit the invention to the details described herein. For example, the embedded wedge-like inserts can be omitted in certain applications wherein the shape of the longitudinal sealing strips and the material thereof is selected such that they serve as wedge-like members to achieve an adequate seal.

## Claims

1. A pipe repair or jointing collar comprising a plurality of arcuate segments with clamping means for drawing the segments together to form the collar around a pipe or around a plurality of pipe ends, with interposition of corresponding deformable sealing means, each arcuate segment having an associated sealing member, each sealing member comprising a pair of longitudinally spaced arcuate sealing strips between the respective ends of which extend a pair of longitudinal sealing strips, rigid wedge-like members being provided within the segments in the regions of the clamping means and adapted to progress generally inwardly with respect to the segments as the latter are drawn together thus to force the sealing members radially inwards in said re-

gions; characterised in that the wedge-like members are non-removably formed with the sealing members.

wherein the shape of each longitudinal sealing strip, and the material thereof is selected such that the longitudinal sealing strips themselves serve as wedge-like members.

2. A pipe repair or jointing collar according to Claim 1, wherein the wedge-like members are embedded within the longitudinal sealing strips which are integrally formed with the arcuate sealing strips thus to form a one-piece sealing means of rectangular form when laid flat. 5  
10
3. A pipe repair or jointing collar according to Claim 1 or Claim 2, wherein the longitudinal sealing strips include at their respective ends a pair of integral lugs each having means for engagement with a part of a respective arcuate segment. 15
4. A pipe repair or jointing collar according to Claim 1, comprising a pair of said arcuate segments and a pair of said sealing means each associated with one of the segments, the longitudinal sealing strips of the pair of sealing means having mutually abutting flat faces, the arcuate sealing strips extending to lie co-planar with said flat faces. 20  
25
5. A pipe repair or jointing collar according to Claim 2, wherein there is provided at each corner defined by a respective arcuate sealing strip and a longitudinal sealing strip a generally triangular strengthening web integrally formed with the arcuate and longitudinal sealing strips. 30
6. A pipe repair or jointing collar according to Claim 1, wherein the arcuate sealing strips are curved about an axis transverse to the longitudinal sealing strips. 35
7. A pipe repair or jointing collar according to Claim 1, wherein the wedge-like members are of cast iron.
8. A pipe repair or jointing collar according to Claim 1, wherein the wedge-like members are of aluminium. 40
9. A pipe repair or jointing collar according to Claim 1, wherein each sealing member comprising the arcuate sealing strips and the longitudinal sealing strips, is formed as one piece integrally of natural or synthetic rubber. 45
10. A pipe repair or jointing collar, according to Claim 1, wherein each arcuate sealing strip has a smooth inner sealing surface. 50
11. A pipe repair or jointing collar according to Claim 1, wherein each longitudinal sealing strip is surrounded by slightly inclined surfaces extending inwardly from the outer edges thereof. 55
12. A pipe repair or jointing collar according to Claim 1,




FIG.1





FIG.2





European Patent  
Office

## EUROPEAN SEARCH REPORT

Application Number  
EP 97 30 1447

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int.Cl.6)
X	GB 2 240 600 A (PEART E & CO LTD) * abstract * * figures 1,2 * * page 2, line 15 - page 3, line 12 * * page 4, line 17 - line 23 * * page 5, line 1 - line 9 * * page 5, line 13 - page 6, line 5 * * page 8, line 15 - page 9, line 1 * * claims 1,2 *	1	F16L55/172
A	---	2-12	
D,A	GB 2 189 000 A (PEART E & CO LTD) * the whole document *	1-12	
A	GB 2 229 245 A (PEART E & CO LTD) * abstract * * figure 2 *	1	
			TECHNICAL FIELDS SEARCHED (Int.Cl.6)
			F16L
The present search report has been drawn up for all claims			
Place of search BERLIN		Date of completion of the search 5 June 1997	Examiner Schaeffler, C
<p><b>CATEGORY OF CITED DOCUMENTS</b></p> <p>X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category. A : technological background O : non-written disclosure P : intermediate document</p> <p>T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date U : document cited in the application L : document cited for other reasons &amp; : member of the same patent family, corresponding document</p>			

EPO FORM 1501 (01.01.1990)